



838 COATINGS

925 Babcock Blvd
Delano, MN 55328

PRODUCT INFORMATION SHEET

838 WebTape

Coating Ready Tape with Web Face

DESCRIPTION

838 WebTape has a facing designed to hold both solvent and water based coatings. Web tape can be used over a variety of roofing substrates including: metal, EPDM, PVC, TPO, CSPE and asphalt.

USES

WebTape can be used on metal to seal roof joints and gutters. It can also be used to seal tears and holes in membranes, flashings, and skylights. WebTape can stick to itself and it can be cut or folded to fit around objects. Surfaces must be clean and dry before

application. Use PlyPrime before installing WebTape on membranes to promote adhesion. Roll web face with pressure after application. Coating must be applied over WebTape applications.

ADVANTAGES

- Use with solvent or water based coatings
- Sticks to a wide variety of substrates
- Apply to temperatures below 0°F
- Available in 4 and 6 inch widths
- Available in off-white

NOTES: For application questions, please call 763-972-9441. See MSDS for additional product information.

838 WebTape Technical Data

| | |
|-------------------------------|---|
| Adhesion | 19 lbs/in width |
| Application Temperature | -20°F to 150°F (air and substrate) |
| Elongation | >500% |
| Water Vapor Test (ASTM E-96B) | 0.005 g/100in ² /24hrs/100°F |
| Total Thickness | 30 mils |
| Roll Sizes | 4" and 6" by 50 ft |