

DESCRIPTION

838 SEAL-FAST is a sprayable, fiber reinforced, sealant designed to seal the seams and fasteners of metal roofs. This 100% acrylic is water based with excellent physical properties (tensile strength and elongation).

USES

838 SEAL-FAST is designed to encapsulate seams and fastener heads on metal roofs with minimal sag. 838 SEAL-FAST can be sprayed in a single application. A consistent sealant thickness minimum of 50 dry mils is required. Do not apply if air temperature is below 42°F or substrate temperature is above 120°F.

PRODUCT INFORMATION SHEET

ADVANTAGES

- Sprayable
- Completely encapsulates seams and fasteners
- Tough Physical Properties - high tensile strength and excellent elongation
- Superior sag resistance
- Water based for easy cleanup
- Warranted - 10 year material warranty
- Available in 5-gallon and 55-gallon

NOTES

For application questions, please call 763-972-9441. See SDS for additional product information.

838 SEAL-FAST Technical Data

Application Rate	1.0 gallon per 80 lineal ft at 3" wide (50 dry mils)
Application Temperature	42°F to 120°F (air and substrate)
Application Method	Spray, extrusion, pour or brush
Water Permiability	5 per inch
Drying Time (75°F and 50% RH)	Approximately 2 to 4 hrs
Total Solids - Volume / Weight	68% / 60%
Weight per Gallon	8.7 lbs
Viscosity (75°F)	20,000 cps 3 15%
Elongation / Tensile Strength	250% 3 30% / 550 ± 30 psi
VOC	< 45 g/l